Provability of Functionnal Reactive Programming type system

Esaïe Bauer Alexis Saurin IRIF – Université de Paris – CNRS – INRIA

Motivation. It has been a decade that a Curry-Howard correspondance between Linear Temporal Logic (LTL) and Reactive Programming has been made (even if correspondance between LTL and other systems has been made before, by Davies [1] for instance). Reactive Programming is a paradigm of programmation where programs receive data over time and maintain properties over time. Linear Temporal Logic is a logic system where a new connective \bigcirc allows us to describe the validity of formulas over time ($\bigcirc A$ means that the formula A will be true in the next time step). In addition to that, LTL helps to express the validity of a formula on at least one time-step in the future or on all time-step in the future with the two connectives \diamondsuit and \square respectively. The system LJ^{\bigcirc} from Kojima and Igarashi [2] does not deal with \square or \diamondsuit , whereas the type system for the Functionnal Reactive Programming FRP from Cave et al. [3] handles it by using fixpoint connectives μ and ν . In order to comply to some Reactive Programming properties such as causality, Temporal Logic has to reject formulas like $\bigcirc(A \lor B) \to \bigcirc A \lor \bigcirc B$ in the general case. The two systems LJ^{\bigcirc} and FRP reject such a formula. One of our goal is to investigate provability of Cave et al. system using Kojima and Igarashi style of presentation. In fact, in Kojima and Igarashi system, time is handled by annotating the formulas of a given sequent with a natural number, which is more suitable for studying provability.

FRP^{\bigcirc} and Kripke Semantic for FRP. As said before, Kojima and Igarashi system deals with temporality by annotating formulas of a sequent. We define a system of rules FRP^{\bigcirc} in the Kojima and Igarashi style [2] together with provability equivalence regarding a μ and ν -free subsystem from FRP [3] and with a cut-elimination result. Here are the two equivalence results:

Proposition 1. If $\Gamma^{\vec{m}} \vdash A^n$ is provable in FRP^{\bigcirc} , then for all $i \leq \min(n, \vec{m})$, $; \bigcirc^{\vec{m}-i}\Gamma \vdash \bigcirc^{n-i}A$ is provable in FRP. **Proposition 2.** If $\Theta; \Gamma \vdash A$ is provable in FRP, then for all $i, \Theta^{i+1}, \Gamma^i \vdash A^i$ is provable in FRP^{\bigcirc} .

When looking at the two systems LJ^{\bigcirc} and FRP^{\bigcirc} , we can easily notice that LJ^{\bigcirc} proves more sequents than FRP^{\bigcirc} and (to a certain extent) than FRP. In particular the formula $(\bigcirc A \to \bigcirc B) \to \bigcirc (A \to B)$ is provable in LJ^{\bigcirc} , but not in FRP^{\bigcirc} .

As Kojima and Igarashi proposed a Kripke semantic for LJ^{\bigcirc} , we propose a Kripke semantic IM_{FRP}^{\bigcirc} by removing the condition of being an IM^{\bigcirc} -frame in [2]. Satisfying all models will be harder for a given formula and it is precisely what we need for our soundness and completeness results relatively to FRP^{\bigcirc} :

Proposition 3. For all Γ and A, the two following statements are equivalent:

- 1. For all IM_{FRP}^{\bigcirc} (W, \leq, R, \Vdash) , and for all $w \in W$, $w \Vdash \Gamma$ implies that $w \Vdash A$.
- 2. The sequent $\Gamma \vdash A$ is provable in FRP^{\bigcirc} .

Future directions. The two systems from [2] and [3] are intuitionistic because intuitionistic systems ensure constructivity. Yet, since Griffin and Parigot's works [4] [5], it has been established that intuitionistic logic was not necessary to ensure constructivity. Another objective would be to consider a classical and constructive type system for FRP together with the fixpoint fragment from FRP (that we forgot with FRP^O). The benefit of such consideration would be to have more elaborate primitives of programmation and to have a better control on the execution of the programs. However, a clear study of what can be proved in such type system has to be done, as the formula $\bigcirc (A \lor B) \rightarrow \bigcirc A \lor \bigcirc B$ seems to be provable in a classical version of LTL.

References

- [1] Rowan Davies. A temporal logic approach to binding-time analysis. J. ACM, 64(1):1:1-1:45, 2017.
- [2] Kensuke Kojima and Atsushi Igarashi. Constructive linear-time temporal logic: Proof systems and kripke semantics. *Information and Computation*, 209(12):1491–1503, 2011. Intuitionistic Modal Logic and Applications (IMLA 2008).
- [3] Andrew Cave, Francisco Ferreira, Prakash Panangaden, and Brigitte Pientka. Fair reactive programming. SIG-PLAN Not., 49(1):361–372, January 2014.
- [4] M. Parigot. Lambda-mu-calculus: An algorithmic interpretation of classical natural deduction. In LPAR, 1992.
- [5] Timothy Griffin. A formulae-as-types notion of control. In Frances E. Allen, editor, Conference Record of the Seventeenth Annual ACM Symposium on Principles of Programming Languages, San Francisco, California, USA, January 1990, pages 47–58. ACM Press, 1990.